



PFMF332S-200
3-LINE + GROUND SCIF/TEMPEST FILTER

SPECIFICATIONS


- MAX VOLTAGE: 0-277/0-480VAC
- MAX CURRENT: 200A/LINE
- FREQUENCY: 50/60HZ
- OPERATING TEMP.: -40 TO 65C
- HIPOT (L-G): 2200VDC
- DISCHARGE VOLT. (@277V): <30V IN 30S
- VOLT. DROP: <2% MAX AT FULL RATED UNITY LOAD
- OVERLOAD: 140% RATED CURRENT FOR 15 MINUTES
- PERFORMANCE: >100dB (14KHZ TO 40GHZ)
- SHIELDING EFFECTIVENESS: >100dB (14KHZ TO 40GHZ)
- ENCLOSURE: NEMA 1 (14GA MINIMUM)
- MANUFACTURED IN ACCORDANCE WITH

THE FOLLOWING STANDARDS:

- MIL-STD-220
- MIL-F-15733
- MIL-STD-810
- MIL-STD-202
- MIL-STD-285
- LV DIRECTIVE



CONFORMS TO
 UL STD 1283



NOTES:

1. CONDUIT CUTOUTS BY END USER.
2. FILTER IS BIDIRECTIONAL. IF INSTALLING FILTER INTERNAL TO SCIF RUN POWER INPUT WIRING INTO FILTER EMI GASKETED OUTPUT COMPARTMENT.

MODEL	AMPS	TERMINAL	DIMENSIONS, MM(IN)					WEIGHT LBS(KG)
			A	B	C	D	E	
PFMF332S-200	200	M12	1067 (42)	558 (22)	254 (10)	483 (19)	608 (24)	240 (109)