

PFMT222S-300
2-LINE + GND TEMPEST FILTER
100dB@10KHZ


SPECIFICATIONS

MAX VOLTAGE: 0-277/0-480VAC
 MAX CURRENT: 300A/LINE
 FREQUENCY: 50/60HZ
 OPERATING TEMP.: -40 TO 70C
 HIPOT (L-G): 2200VDC
 (PRIOR TO INSTALLING DISCHARGE RESISTORS)
 DISCHARGE VOLT. (@277V): <30V IN 30S
 OVERLOAD: 140% RATED CURRENT FOR 15 MINUTES
 PERFORMANCE: >100dB (10KHZ TO 20GHZ)
 DESIGNED IN ACCORDANCE WITH THE
 FOLLOWING STANDARDS:

MIL-STD-220
 MIL-F-15733
 MIL-STD-810
 LV DIRECTIVE



CONFORMS TO
 UL STD 1283



MODEL	AMPS	TERMINALS	DIMENSIONS (MM)									WEIGHT LBS(KG)
			A	B	C	D	E	F	G	H	I	
PFMT222S-300	300	M16	711	229	178	610	269	55	119	89	114.5	115 (52.3)
			(28)	(9)	(7)	(24)	(10.6)	(2.2)	(4.7)	(3.5)	(4.5)	