



## PFMT355S-600 3-LINE + GND TEMPEST FILTER

### SPECIFICATIONS

MAX VOLTAGE: 0-277/0-480VAC

MAX CURRENT: 600A/LINE

FREQUENCY: 50/60HZ

OPERATING TEMP.: -40 TO 70C

HIPOT (L-G): 2200VDC

(PRIOR TO INSTALLING DISCHARGE RESISTORS)

DISCHARGE VOLT. (@277V): <30V IN 30S

OVERLOAD: 140% RATED CURRENT FOR 15 MINUTES

PERFORMANCE: >100dB (10KHZ TO 40GHZ)

SHIELDING EFFECTIVENESS: >100dB (10KHZ TO 40GHZ)

ENCLOSURE: NEMA 1 (14GA MINIMUM)

MANUFACTURED IN ACCORDANCE WITH

THE FOLLOWING STANDARDS:

MIL-STD-220

MIL-F-15733

MIL-STD-810


LV DIRECTIVE



5025116

CONFORMS TO  
UL STD 1283

GASKETED OUTPUT  
COMPARTMENT



### NOTES:

1. CONDUIT CUTOUTS BY END USER.
2. FILTER IS BIDIRECTIONAL. IF INSTALLING FILTER INTERNAL TO SCIF RUN POWER INPUT WIRING INTO FILTER EMI GASKETED OUTPUT COMPARTMENT.
3. GROUND STUD LOCATED IN INPUT AND OUTPUT COMPARTMENTS.

MODEL	AMPS	TERMINALS	DIMENSIONS - MM (IN)					WEIGHT LBS(KG)
			A	B	C	D	E	
PFMT355S-600	600	2xM16	1677	762	381	762	813	395(179.5)
			(66)	(30)	(15)	(30)	(32)	